

	Description			Mechanical specifications					Electrical specifications		
	Code	Type		rpm		Centrifugal force		Weight kg	Max input power W	Max. current A	
				50 Hz	60 Hz	50 Hz	60 Hz			50 Hz	380/480 V 50/60 Hz
three-phase	600290	M3/4	□	3000	3600	4	6	0.92	24	-	-
	600291	M3/20	□	3000	3600	20	29	1.97	35	0.15	-
	600292	M3/45	□	3000	3600	45	65	2.20	45	0.16	-
single-phase	600290	M3/4	□	3000	3600	4	6	0.92	24	0.13	0.30
	600291	M3/20	□	3000	3600	20	29	1.97	35	0.17	0.42
	600292	M3/45	□	3000	3600	45	65	2.20	45	0.20	0.46

* The CSA version can be supplied on request and does not envision supply of the condenser.

		Dimensional specifications (mm)																	
		Fig.	A	B	C	D	D1	E	E1	F	G	Fori øG1	N°	H	I	L	M	N	Cable entry thread
three-phase	M3/4	N	113	62.5	90	25-40	-	75	-	9	5.5	-	4	32	20	56.6	59	61	M12x1.5
	M3/20	N	154	74.5	110	25-40	60	92	85	9	6.5	6.5	8	38	27.5	68.6	83	73	M16x1.5
	M3/45	N	169	74.5	110	25-40	60	92	85	9	6.5	6.5	8	38	35	68.6	83	73	M16x1.5
single-phase	M3/4	N	113	62.5	90	25-40	-	75	-	9	5.5	-	4	32	20	56.6	59	61	M12x1.5
	M3/20	N	154	74.5	110	25-40	60	92	85	9	6.5	6.5	8	38	27.5	68.6	83	73	M16x1.5
	M3/45	N	169	74.5	110	25-40	60	92	85	9	6.5	6.5	8	38	35	68.6	83	73	M16x1.5

